

DECLARATION OF PERFORMANCE NO 06CE/BIII/CSE/04

1. The unique identification code of the product type: **06/BIII/GL/CSE**
2. Intended use or use:
Dry-pressed ceramic tiles with water absorption equal to $E_b > 10\%$; Annex K; BIII group, glazed (GL); for interior walls of buildings - as described on the packaging.
3. Manufacturer: **CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce**
4. System(s) of assessment and verification of constancy of performance: **SYSTEM 4**
5. Harmonised standard: **EN 14411:2012**
6. Declared performance:

<i>Essential characteristics</i>	<i>Performance (level and/or class)</i>	<i>Harmonised technical specification</i>
Reaction-to-fire performance	A1	Classified Without Testing (CWT) EN 14411:2012
Release of dangerous substances:		
- Cadmium	Max 0,07mg/dm ²	
- Lead	Max 0,8mg/dm ²	
Bond strength/adhesion [N/mm²]:		
- cementitious adhesives	NPD - No Performance Determined	
- dispersion adhesives		
- reaction resin adhesives		
- mortar		
Thermal shock resistance	Meets	
Durability for:		
- internal use:	Meets	
- external use: resistance to freeze-thaw cycles	Does not meet	

A copy of the Declaration of Performance is available on the website: www.cersanit.com

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Signed on behalf of the manufacturer:

QUALITY SYSTEM MANAGER


Joanna Grzebna

Kielce, 01.06.2017
(place and date of issue)

.....
(signature)