

DECLARATION OF PERFORMANCE

No 04/1 UKCA/Bla/01

1. THE UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE: Dry pressed ceramic tiles with low water absorption $E_b \leq 0,5\%$; Annex G, Bla Group, glazed (GL); polished

2. INTENDED USE OR USES: For walls and floors internal and for walls external, in buildings and industrial facilities.

3. MANUFACTURER: CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce

4. SYSTEM(S) OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE: SYSTEM 4

5. HARMONIZED STANDARD: EN 14411:2012

6. DECLARED PERFORMANCE:

| ESSENTIAL CHARACTERISTICS | PERFORMANCE (LEVEL AND/OR CLASS) |
|---|---|
| Reaction-to-fire performance | A1 / A1 _{FL} Classified Without Testing (CWT) |
| Release of dangerous substances: | |
| - Cadmium | $\leq 0,07 \text{ mg/dm}^2$ |
| - Lead | $\leq 0,8 \text{ mg/dm}^2$ |
| Breaking strength: | |
| - thickness $\geq 7,5 \text{ mm}$ | $\geq 1300 \text{ N}$ |
| Bond strength/adhesion [N/mm²]: | |
| - cementitious adhesives | $\geq 0,5 \text{ N/mm}^2$ |
| - dispersion adhesives | $\geq 1 \text{ N/mm}^2$ |
| - reaction resin adhesives | $\geq 2 \text{ N/mm}^2$ |
| - mortar | NPD |
| Slippage according to CEN/TS 16165:2012, Annex B | NPD - No Performance Determined |
| Thermal shock resistance | Pass |
| Durability for: | |
| - internal use: | Pass |
| - external use: resistance to freeze-thaw cycles | Pass |
| Tactility | NPD |

A copy of the Declaration of Performance is available on the website: www.cersanit.com; www.opoczno.eu

The performance of the product(s) identified above is/are in conformity with the declared performance in the table above. This Declaration Of Performance is issued under the sole responsibility of the manufacturer identified above

Place, date:
Kielce, 01.04.2022

Signed on behalf of the manufacturer

QUALITY DIRECTOR
CERSANIT S.A.

Jolanta Grzebna