cersanit

DECLARATION OF PERFORMANCE NO 07CE/BIb/CSE/04

1. The unique identification code of the product type: **07/BIb/UGL/CSE**
2. Intended use or use:

   Dry-pressed ceramic tiles with water absorption equal to 0,5%<E_b≤3%; Annex H; BIb group, unglazed (UGL), clinker; for interior and exterior walls and floors of buildings - as described on the packaging.
3. Manufacturer: **CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce**
4. System(s) of assessment and verification of constancy of performance: ***SYSTEM 4***
5. Harmonised standard: **EN 14411:2012**
6. Declared performance:

Essential characteristics	***Performance (level and/or class)***	***Harmonised technical specification***
Reaction-to-fire performance	*$A1_{FL}$*	*Classified Without Testing (CWT)*
Release of dangerous substances:		EN 14411:2012
- Cadmium	*Max 0,07mg/dm²*	
- Lead	*Max 0,8mg/dm²*	
Breaking strength:		
- thickness ≥7,5mm	*≥ 1100N*	
- thickness <7,5mm	*≥ 700N*	
Bond strength/adhesion [N/mm2]:		
- cementitious adhesives	*NPD - No Performance Determined*	
- dispersion adhesives		
- reaction resin adhesives		
- mortar		
Slippage according to CEN/TS 16165:2012, Annex B	*NPD – R13*	
Thermal shock resistance	*Meets*	
Durability for:		
- internal use:	*Meets*	
- external use: resistance to freeze-thaw cycles	*Meets*	
Tactility	*NPD - No Performance Determined*	

A copy of the Declaration of Performance is available on the website: www.cersanit.com

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Signed on behalf of the manufacturer:

QUALITY SYSTEM MANAGER
Jolanta Grzebna

Kielce, 01.06.2017
(place and date of issue)

.....
(signature)